


## HARPER 330

Cod. HP330AA000140



### Introduction

HARPER330 series self-contained LED signalling light with self-extinguishing RAL9003 white polycarbonate body and PMMA diffuser. Wall, flag, ceiling/false ceiling, suspended mount. Power supply 220/230 Vac, 50-60 Hz. Type Maintained; luminosity settable in Maintained mode. Rechargeable LiFePO<sub>4</sub> battery @ 1.5 Ah included; charging time 6 h; minimum autonomy 1 h. Function/Malfunction signalling LEDs. Protection rating IP40, double insulated, operating temperature 0 °C ÷ 50 °C. Dimensions: 231.5 x 322 x 41 mm.

### Description

|                |                                             |
|----------------|---------------------------------------------|
| Product series | HARPER 330                                  |
| Product type   | Signalling luminaire                        |
| Version        | Self-Test (Self-diagnosis)                  |
| Type           | Maintained                                  |
| Dimensions     | Height 231.5 mm, Length 322 mm, Depth 41 mm |

### Technical specifications

|                              |                                                                                                       |
|------------------------------|-------------------------------------------------------------------------------------------------------|
| Installation                 | Wall, flag, ceiling, false ceiling, suspended mount                                                   |
| Power supply                 | 220/230 Vac, 50-60 Hz                                                                                 |
| Absorbed power in W          | 4.8 W                                                                                                 |
| Maximum absorbed power in VA | 8 VA                                                                                                  |
| Battery                      | N.1 LiFePO <sub>4</sub> 3.2 V 1.5 Ah                                                                  |
| Autonomy                     | 1 h                                                                                                   |
| Total charging time          | 6 h                                                                                                   |
| Visibility distance          | 30 m                                                                                                  |
| Light source                 | LED                                                                                                   |
| Number of LEDs               | 20                                                                                                    |
| Colour temperature           | 6000 K                                                                                                |
| Body                         | RAL9003 White Polycarbonate                                                                           |
| Glow wire                    | 850 °C                                                                                                |
| Diffuser                     | Silk-screened PMMA (sold separately/accessory)                                                        |
| IP Protection rating         | IP40                                                                                                  |
| IK Protection rating         | IK07                                                                                                  |
| Insulation class             | II                                                                                                    |
| Operating temperature        | 0° - 50°C                                                                                             |
| Additional information       | Dedicated terminals for <i>inhibit mode</i> and <i>rest mode</i><br>Test button and brightness dimmer |
| Compliant to standards       | EN 60598-1, EN 60598-2-22, EN 62471<br>EN 1838, ISO3864-4, ISO 7010                                   |
| Photobiological risk         | RG0 (exempt) according to EN 62471                                                                    |