


HARPER 330

Cod. HP330AA000340



Introduction

HARPER330 series self-contained LED signalling light with self-extinguishing RAL9003 white polycarbonate body and PMMA diffuser. Wall, flag, ceiling/false ceiling, suspended mount. Power supply 220/230 Vac, 50-60 Hz. Type Maintained; luminosity settable in Maintained mode. Rechargeable LiFePO₄ battery @ 3.3 Ah included; charging time 12 h; minimum autonomy 3 h. Function/Malfunction signalling LEDs. Protection rating IP40, double insulated, operating temperature 0 °C ÷ 50 °C. Dimensions: 231.5 x 322 x 41 mm.

Description

Product series	HARPER 330
Product type	Signalling luminaire
Version	Self-Test (Self-diagnosis)
Type	Maintained
Dimensions	Height 231.5 mm, Length 322 mm, Depth 41 mm

Technical specifications

Installation	Wall, flag, ceiling, false ceiling, suspended mount
Power supply	220/230 Vac, 50-60 Hz
Absorbed power in W	4.8 W
Maximum absorbed power in VA	8 VA
Battery	N.1 LiFePO ₄ 3.2 V 3.3 Ah
Autonomy	3 h
Total charging time	12 h
Visibility distance	30 m
Light source	LED
Number of LEDs	20
Colour temperature	6000 K
Body	RAL9003 White Polycarbonate
Glow wire	850 °C
Diffuser	Silk-screened PMMA (sold separately/accessory)
IP Protection rating	IP40
IK Protection rating	IK07
Insulation class	II
Operating temperature	0° - 50°C
Additional information	Dedicated terminals for <i>inhibit mode</i> and <i>rest mode</i> Test button and brightness dimmer
Compliant to standards	EN 60598-1, EN 60598-2-22, EN 62471 EN 1838, ISO3864-4, ISO 7010
Photobiological risk	RG0 (exempt) according to EN 62471