


HARPER 330

Cod. HP330BA000340



Introduction

HARPER330 series self-contained LED signalling light with self-extinguishing RAL9003 white polycarbonate body and PMMA diffuser. Wall, flag, ceiling/false ceiling, suspended mount. Power supply 220/230 Vac, 50-60 Hz. Type Maintained; luminosity settable in Maintained mode. Rechargeable LiFePO₄ battery @ 3.3 Ah included; charging time 12 h; minimum autonomy 3 h. Function/Malfuction signalling LEDs. Integrated module for centralized diagnosis. Protection rating IP40, double insulated, operating temperature 0 °C ÷ 50 °C. Dimensions: 231.5 x 322 x 41 mm.

Description

Product series	HARPER 330
Product type	Signalling luminaire
Version	BUS Supervised
Type	Maintained
Dimensions	Height 231.5 mm, Length 322 mm, Depth 41 mm

Technical specifications

Installation	Wall, flag, ceiling, false ceiling, suspended mount
Power supply	220/230 Vac, 50-60 Hz
Absorbed power in W	4.8 W
Maximum absorbed power in VA	8 VA
Battery	N.1 LiFePO ₄ 3.2 V 3.3 Ah
Autonomy	3 h
Total charging time	12 h
Visibility distance	30 m
Light source	LED
Number of LEDs	20
Colour temperature	6000 K
Body	RAL9003 White Polycarbonate
Glow wire	850 °C
Diffuser	Silk-screened PMMA (sold separately/accessory)
IP Protection rating	IP40
IK Protection rating	IK07
Insulation class	II
Operating temperature	0° - 50°C
Additional information	Test button and brightness dimmer
Compliant to standards	EN 60598-1, EN 60598-2-22, EN 62471 EN 1838, ISO3864-4, ISO 7010
Photobiological risk	RG0 (exempt) according to EN 62471