

SPOTLEDCod. **SPLA240040****Introduction**

SPOTLED series LED emergency light for centralized power supply system with self-extinguishing RAL9003 white polycarbonate body. False ceiling installation. Power supply 220/230 Vac, 50-60 Hz. Luminous flux 300 lm. Symmetrical and Asymmetrical optics included.

Protection rating IP40, double insulated, operating temperature 0 °C ÷ 40 °C.

Description

Product series	SPOTLED
Product type	Emergency luminaire
Version	Central Battery (centralized power supply)
Type	-
Module dimensions	230 x 65 x 26 mm
Spotlight diameter	90 mm

Technical specifications

Installation	False ceiling
Power supply	220/230 V~, 50-60 Hz
Absorbed power in W	4.3 W
Max absorbed power in VA	6.7 VA
Battery	-
Autonomy	-
Total charging time	-

Driver Body	White Polycarbonate RAL9003
Spotlight Frame	White Polycarbonate RAL9003
Glow wire	850 °C
IP Protection rating	IP40
IK Protection rating	IK07
Insulation class	II
Operating temperature	0° - 40°C
Compliant to standards	EN 60598-1, EN 60598-2-22, EN 61547 EN 55015, EN 61000-3-2, EN 61000-3-3 EN 61347-1, EN 61347-2-7

Light source	LED
Colour temperature	5700K
Luminous flux	300 lm

A = mm 230
B = mm 240,2
C = mm 65
D = mm 26
F = Ø 90
E = Ø 74

