

HARPER 200Cod. **HP200SE110465**CE  **IP65****Introduction**

HARPER200 series self-contained LED emergency light with self-extinguishing RAL9003 white polycarbonate body and PMMA reflector with no photobiological risk (RG0). Wall, ceiling and flush mount installation. Power supply 220/230 Vac, 50-60 Hz. Type Non-Maintained or Public Show; luminous flux in emergency 180 lm. Rechargeable LiFePO₄ battery @ 3.3 Ah included; charging time 24 h; minimum autonomy 4 h. Protection rating IP65, double insulated, operating temperature 0 °C ÷ 50 °C. Dimensions: 137 x 319 x 38 mm.

Description

Product series	HARPER 200
Product type	Emergency luminaire
Version	Standard
Type	Non-Maintained, Public Show
Dimensions	Height 137 mm, Length 319 mm, Depth 38 mm

Technical specifications

Installation	Wall, ceiling, surface/false ceiling mount
Power supply	220/230 Vac, 50-60 Hz
Absorbed power in W	1 W
Current absorbed from Mains	120 mA
Battery	N.1 LiFePO ₄ 3.2 V 3.3 Ah
Autonomy	4 h
Total charging time	24 h

Body	White Polycarbonate RAL9003
Glow wire	850 °C
Diffuser	PMMA laser finish
IP Protection rating	IP65
IK Protection rating	IK07
Insulation class	II
Operating temperature	0° - 50°C
Additional information	Test button
Compliant to standards	EN 60598-1, EN 60598-2-22, EN 61547, EN 55015 EN 61000-3-2, EN 61000-3-3, EN 61347-1, EN 61347-2-7
Photobiological risk	RG0 (exempt) according to EN 62471

Light source	LED
Colour temperature	6000K
Min. luminous flux in emergency	180 lm
Lum. flux in Maintained mode	-

